

INLAND TECHNOLOGY -- SKYSOL 200,FS 200 - CLEANING COMPOUND, SOLVENT  
MATERIAL SAFETY DATA SHEET  
NSN: 6850013814427  
Manufacturer's CAGE: OK209  
Part No. Indicator: A  
Part Number/Trade Name: SKYSOL 200,FS 200

=====

General Information

=====

Item Name: CLEANING COMPOUND, SOLVENT  
Company's Name: INLAND TECHNOLOGY INC  
Company's Street: 401 EAST 27TH STREET  
Company's City: TACOMA  
Company's State: WA  
Company's Country: US  
Company's Zip Code: 98421  
Company's Emerg Ph #: 800-255-3924  
Company's Info Ph #: 800-552-3100/206-383-1177/838-9889  
Record No. For Safety Entry: 001  
Tot Safety Entries This Stk#: 001  
Status: SE  
Date MSDS Prepared: 13OCT94  
Safety Data Review Date: 07FEB95  
Supply Item Manager: CX  
MSDS Preparer's Name: UNKNOWN  
MSDS Serial Number: BSGM/  
Specification Number: NONE  
Spec Type, Grade, Class: NONE  
Hazard Characteristic Code: F8  
Unit Of Issue: CN  
Unit Of Issue Container Qty: 5 GAL  
Type Of Container: CAN  
Net Unit Weight: 32.5 LBS  
NRC/State License Number: NOT RELEVANT

=====

Ingredients/Identity Information

=====

Proprietary: NO  
Ingredient: MINERAL SPIRITS/C12-C13 PARAFFINIC HYDROCARBONS  
Ingredient Sequence Number: 01  
Percent: UNKNOWN  
NIOSH (RTECS) Number: PY8240000  
CAS Number: 64475-85-0  
OSHA PEL: 5 MG/M3 AS OIL MIST  
ACGIH TLV: 5 MG/M3 AS OIL MIST  
Other Recommended Limit: NONE RECOMMENDED

-----

Proprietary: NO  
Ingredient: D-LIMONENE  
Ingredient Sequence Number: 02  
Percent: UNKNOWN  
NIOSH (RTECS) Number: 1006452DL  
CAS Number: 5989-27-5  
OSHA PEL: NOT ESTABLISHED  
ACGIH TLV: NOT ESTABLISHED  
Other Recommended Limit: NONE RECOMMENDED

=====

**Physical /Chemical Characteristics**

=====

Appearance And Odor: CLEAR LIQUID WITH MILD CITRUS ODOR  
Boiling Point: 340F, 171C  
Melting Point: UNKNOWN  
Vapor Pressure (MM Hg/70 F): <2 @ 77F  
Vapor Density (Air=1): >4  
Specific Gravity: 0.78  
Decomposition Temperature: UNKNOWN  
Evaporation Rate And Ref: <0.1 (N-BUTYL ACETATE=1)  
Solubility In Water: INSOLUBLE  
Percent Volatiles By Volume: 100  
Corrosion Rate (IPY): UNKNOWN

=====

**Fire and Explosion Hazard Data**

=====

Flash Point: 144F, 62C  
Flash Point Method: PMCC  
Lower Explosive Limit: 0.6%  
Upper Explosive Limit: 7%  
Extinguishing Media: FOAM, DRY CHEMICAL, WATER SPRAY OR CARBON DIOXIDE.  
Special Fire Fighting Proc: WEAR AIR-SUPPLIED BREATHING EQUIPMENT AND FULL PROTECTIVE GEAR FOR ENCLOSED OR CONFINED SPACES OR AS OTHERWISE NEEDED.  
Unusual Fire And Expl Hazrds: NONE KNOWN.

=====

**Reactivity Data**

=====

Stability: YES  
Cond To Avoid (Stability): FLAME, SPARKS, EXCESSIVE HEAT  
Materials To Avoid: STRONG OXIDIZING AGENTS, STRONG ACIDS.  
Hazardous Decomp Products: CARBON MONOXIDE AND CARBON DIOXIDE, HYDROCARBONS.  
Hazardous Poly Occur: NO  
Conditions To Avoid (Poly): NOT RELEVANT

=====

**Health Hazard Data**

=====

LD50-LC50 Mixture: TLV; 5 MG/M3 AS OIL MIST  
Route Of Entry - Inhalation: YES  
Route Of Entry - Skin: YES  
Route Of Entry - Ingestion: NO  
Health Haz Acute And Chronic: TARGET ORGANS: EYE, SKIN, RESPIRATORY TRACT.  
ACUTE- MISTS MAY CAUSE RESPIRATORY TRACT IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. LOW ORDER ORAL AND DERMAL TOXICITY. CHRONIC- PROLONGED OR REPEATED SKIN EXPOSURE CAN LEAD TO MILD IRRITATION, DEFATTING AND DERMATITIS.  
Carcinogenicity - NTP: NO  
Carcinogenicity - IARC: NO  
Carcinogenicity - OSHA: NO  
Explanation Carcinogenicity: NONE  
Signs/Symptoms Of Overexp: EYES, SKIN, RESPIRATORY TRACT IRRITATION  
Med Cond Aggravated By Exp: SKIN CONTACT MAY AGGAVATE EXISTING DERMATITIS.  
Emergency/First Aid Proc: GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED.  
EYES: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. ORAL: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO

THE LUNGS. GET IMMEDIATE MEDICAL ATTENTION.

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND, EARTH/USE PUMP (EXPLOSION PROOF). GROUND ALL HANDLING EQUIPMENTS. PREVENT LIQUID FROM ENTERING SEWERS.

Neutralizing Agent: NOT RELEVANT

Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Precautions- Handling/Storing: USE AND STORE AWAY FROM SOURCES OF IGNITION, STRONG OXIDIZING AGENTS AND STRONG ACIDS. KEEP CONTAINER SEALED WHEN NOT IN USE.

Other Precautions: DO NOT GET IN EYES, ON SKIN OR ON CLOTHING. WASH THOROUGHLY AFTER HANDLING. AVOID BREATHING OIL MIST. KEEP OUT OF REACH OF CHILDREN.

Control Measures

Respiratory Protection: NONE NORMALLY REQUIRED.

Ventilation: USE ADEQUATE MECHANICAL DILUTION VENTILATION WHENEVER PRODUCT IS USED IN A CONFINED SPACE, HEATED ABOVE ROOM TEMPERATURE

Protective Gloves: NITRILE, IF NEEDED

Eye Protection: SPLASH GOGGLES IF EYE CONTACT POSSIBLE

Other Protective Equipment: EYE WASH STATION, UNIFORM IF REQUIRED

Work Hygienic Practices: WASH HANDS AFTER USE AND BEFORE EATING, DRINKING, OR SMOKING. LAUNDER CONTAMINATED CLOTHES BEFORE REUSE.

Transportation Data

Trans Data Review Date: 95038

DOT PSN Code: ZZZ

DOT Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

IMD PSN Code: ZZZ

IMD Proper Shipping Name: NOT REGULATED FOR THIS MODE OF TRANSPORTATION

IATA PSN Code: ZZZ

IATA Proper Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

AFI PSN Code: ZZZ

AFI Prop. Shipping Name: NOT REGULATED BY THIS MODE OF TRANSPORTATION

Disposal Data

Label Data

Label Required: YES

Technical Review Date: 07FEB95

MFR Label Number: NOT RELEVANT

Label Status: F

Common Name: SKYSOL 200, FS 200

Signal Word: WARNING!

Acute Health Hazard-Slight: X

Contact Hazard-Slight: X

Fire Hazard-Moderate: X

Reactivity Hazard-None: X

Special Hazard Precautions: TARGET ORGANS: EYE, SKIN, RESPIRATORY TRACT.

ACUTE- MISTS MAY CAUSE RESPIRATORY TRACT IRRITATION. EYE CONTACT MAY CAUSE IRRITATION. LOW ORDER ORAL & DERMAL TOXICITY. CHRONIC- CAN LEAD TO MILD IRRITATION, DEFATTING & DERMATITIS. STORE AWAY FROM SOURCES OF IGNITION & INCOMPATIBLES. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT SUCH AS SAND. FIRST AID- GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALED: IF OVERCOME BY VAPORS, REMOVE TO FRESH AIR. PROVIDE CPR/OXYGEN IF NEEDED. EYES: FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN: WASH WITH SOAP & WATER. ORAL: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION.

Protect Eye: Y

Protect Skin: Y

Label Name: INLAND TECHNOLOGY INC

Label Street: 401 EAST 27TH STREET

Label City: TACOMA

Label State: WA

Label Zip Code: 98421

Label Country: US

Label Emergency Number: 800-255-3924

Year Procured: 1995